

Apache Lifts

— a division of Hergott Automotive Equipment Inc.



Model#: AP10TS

Trisymmetric installation
Asymmetric application
10,000 lb. 2-Post Lift


**10,000 LB
2-POST LIFT**

The AP10TS features Apache's innovative Trisymmetric design, providing technicians the versatility to lift vehicles both symmetrically and asymmetrically within the same service bay or install the lift in an asymmetric only configuration. This enables you to have the lift you want the way you want.

With adjustable height and width options, double telescoping screw pads, durable powder coat finish, plated arm restraints and pins and many other appealing features, the AP10TS will accommodate the rigorous demands of a full service facility – and afford room to grow with its reasonable cost. Available in red and blue.

FEATURES & BENEFITS:

- 3-stage front arms provide greater overall arm sweep
- Set up in a symmetric or asymmetric configuration
- Adjustable height and width options accommodate varying service bay sizes
- Double Telescoping Screw Pads adjust to multiple heights minimizing the need for adapters
- Rubber foot pads minimize stress to vehicles with delicate undercoatings
- Padded overhead shut off system prevents vehicle damage
- Single-point mechanical lock release system allows technician to disengage both columns simultaneously
- Wide rubber door guards protects vehicle from door damage
- Premium powder coat finish provides long-lasting durability
- Plated Arm Restraints and Arm Pins inhibit rust and provide long-lasting durability
- Mirrored "S" shaped column provides:
 - maximized strength
 - more surface area for reliable bearing contact
 - provides clear and safe concave conduit for the bearings



FOR MORE INFORMATION CONTACT YOUR AUTHORIZED APACHE LIFTS DISTRIBUTOR

AP10TS

	Symmetric Application	Asymmetric Application
Lifting Capacity*	10,000 lbs.	
Rise Height ¹	74½"	
Overall Height	11' 4½" / 11' 10½"	
Overall Height (Cylinder Extended)	11' 10½"	
Overall Width ³	10' 9" / 11' 3"	10' 11½" / 11' 5½"
Drive-Thru Clearance	92¾" / 98¾"	88½" / 94½"
Floor to Overhead Switch	131" ⅛" / 137" ⅛"	
Short Arm Reach	22¾" - 41½"	
Long Arm Reach	38¼" - 59"	
Screw Pad Height ²	4 ⅜" - 6½"	
Inside of Columns	106¾" / 112¾"	101½" / 107½"
Motor	2HP, Single Phase, 60Hz	
Voltage	208-230v	
Speed of Rise	48 Seconds	
Max Load Per Arm	2,500 lbs.	
Ceiling Height Required	12'	

*Lift capacity ratings are based on loads equally distributed on all four arms.

¹ Rise height is measured with adjustable screw pads in highest position.

² Specifications are listed without rubber pad, for measurements with rubber pad add ¼" (6mm).

³ Overall Width of Asymmetric lift is 11' 3" / 11' 9" including Power Unit.

† Frame engaging adapters (10314 or 10318) are REQUIRED when lifting vehicles with frame construction.


TRISYMMETRIC

Apache Lifts enable you to lift both symmetrically and asymmetrically within the same service bay or install the lift in an asymmetric only configuration. This feature allows you to have the lift you want installed the way you want. No other lift offers the same amount of reliability and versatility




Model#: AP10TS
Asymmetric Only Installation
Asymmetric Application

ARM COVERAGE



Symmetrical Configuration

3-Stage front and 2-Stage rear arms.



Asymmetrical Configuration

3-Stage front and 2-Stage rear arms.



The Automotive Lift Institute (ALI) certifies that the AP10TS described herein comply with the applicable provisions of the American National Standards ANSI/ALI ALCTV 1998 and are Third Party Validated by the ETL Testing Laboratory.

Apache Lifts Innovations
a division of Hergott
Automotive Equipment Inc.
37 McAllister Dr.
Bloomington ON, NOB 1K0

800-461-1692
p: 519-658-3738
f: 519-569-7249
lifts@canada.com

Apache Lifts Innovations reserves the right to make changes to specifications without notice and without making changes retroactive. Unloading, installation and oil not included.